

MODELING SEWER OVERFLOW OF KARBALA CITY WITH LARGE FLOATING POPULATION

HUSSEIN ABED OBAID

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Civil Engineering)

Faculty of Civil Engineering
Universiti Teknologi Malaysia

DECEMBER 2015

This work I dedicate to:

My beloved father and my beloved mother

My faithful wife and my sons, Ali, Murtadah, Mohammed, Baqer, Fatimahalzahrah

My brothers and sisters

My homeland Iraq

For always standing by my side through ups and downs without even a slightest sigh

ACKNOWLEDGEMENT

Praise is to almighty Allah, “Taught man that which he knew not.” My thanks and appreciations go to my Supervisor Assoc. Prof. Dr. Shamsuddin Shahid for his guidance, patience, motivation, support, and advices during my research.

A special thank to Assoc. Prof. Dr. Shreeshivadasan Chelliapan and Dr. Basim Nile for their kindness and their precious help. My appreciation goes to all academic and technical staffs of Civil Engineering faculty, UTM.

ABSTRACT

The sewer systems of many historical or religious cities are not well associated with present needs. Sudden influx of huge floating population during sacred or festival periods places tremendous pressure on utility services including the sewer system in such cities. Sewer overflow, inundation of roads, environmental degradation, and consequent epidemics are very common during such gatherings. Modeling of sewer quantity and quality with varying population is, therefore, very important for cities with a large floating population in order to mitigate the problem. The major objective of this study is to develop a model to assess the impacts of floating population on sewer systems during pilgrimage, in order to proffer necessary mitigation measures. The Karbala city of Iraq was chosen as a case study in the present research. Statistical and physically based models such as Storm Water Management Model (SWMM), Multiple Linear Regression (MLR), Structural Equation Model (SEM) and Artificial Neural Network (ANN) were used for this purpose. The model outputs were analyzed to assess possible changes in sewer discharge and quality in the context of increasing population. Different adaptation measures were also assessed and suitable adaptation measures were identified for mitigating the impacts. The results showed that sewer flow in Karbala city typically increased in the range of 0.009492-0.0144 m³/s for every population rise of one thousand, measured at 95% confidence interval. On the other hand, the concentrations of total suspended solid (TSS) and Biochemical Oxygen Demand (BOD₅) increased by 26-46 mg/L and 9-19 mg/L, respectively at 95% confidence interval, for every 1mm increase in rainfall. BOD₅ was also found to increase by 4-17 mg/L for every ten thousand increase in population. The temporal and spatial modeling of sewer overflow shows that it mostly happens during prayer times and in the upstream area, as the sewer system in the region is incapable of carry in a huge inflow of sewer during those periods. The assessment of different technical measures revealed that pipe-jacking system is the most suitable approach in Karbala city for reducing sewer overflow by up to 70%, if properly installed and managed.

ABSTRAK

Sistem pembentung di kebanyakan bandar bersejarah dan keagamaan adalah tidak memenuhi keperluan semasa. Peningkatan kemasukan secara tiba-tiba jemaah secara besar semasa tempoh suci atau perayaan memberi tekanan yang besar kepada sistem utiliti termasuk sistem pembentung di bandar-bandar tersebut. Limpahan pembentung, banjir jalanraya, pencemaran alam sekitar dan wabak penyakit adalah sangat biasa semasa tempoh perhimpunan tersebut. Pemodelan kuantiti dan kualiti pembentung dengan populasi berbeza adalah sangat penting untuk bandar-bandar dengan kemasukan populasi terapung yang besar sebagai langkah untuk mengurangkan masalah tersebut. Objektif utama kajian ini adalah untuk membangunkan sebuah model untuk menilai kesan jemaah kepada sistem pembentung semasa mengerjakan Haji, dalam usaha untuk mencadangkan langkah-langkah pengurangan yang perlu. Bandar Karbala Iraq telah dipilih sebagai kajian kes dalam kajian ini. Model statistik dan berasaskan fizikal seperti Model Pengurusan Air Banjir (SWMM), Regresi Linear Berganda (MLR), Model Persamaan Struktur (SEM) dan Rangkaian Neural Buatan (ANN) telah digunakan untuk tujuan kajian ini. Output model dianalisa untuk menilai kemungkinan perubahan pelepasan pembentung dan kualiti dalam konteks populasi yang semakin meningkat. Langkah-langkah penyesuaian yang berbeza juga dinilai dan langkah-langkah penyesuaian sesuai telah dikenalpasti untuk mengurangkan kesan. Hasil kajian menunjukkan bahawa aliran pembentung di bandar Karbala biasanya meningkat dalam julat 0.009492-0.0144 m³/s untuk setiap kenaikan satu ribu penduduk, diukur pada selang keyakinan 95%. Sebaliknya, kepekatan jumlah pepejal terampai (TSS) dan Keperluan Oksigen Biokimia (BOD₅) meningkat sebanyak 26-46 mg/L dan 9-19 mg/L, masing-masing pada selang keyakinan 95%, bagi setiap peningkatan 1 mm dalam hujan. BOD₅ juga didapati meningkat sebanyak 4-17 mg/L bagi setiap peningkatan sepuluh ribu penduduk. Pemodelan ruang dan masa pembentung limpahan menunjukkan bahawa ia kebanyakannya berlaku pada waktu solat dan di kawasan hulu sungai, kerana sistem pembentung di rantau ini tidak mampu membawa aliran masuk pembentung yang besar semasa tempoh-tempoh tersebut. Penilaian terhadap langkah-langkah teknikal yang berbeza menunjukkan bahawa sistem paip-pemicu adalah pendekatan yang paling sesuai di bandar Karbala untuk mengurangkan limpahan pembentung sehingga 70%, jika dipasang dan diuruskan dengan betul.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xiii
	LIST OF ABBREVIATIONS	xix
	LIST OF APPENDICES	xxi
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Background of the problem	3
	1.3 Statement of the problem	7
	1.4 Objective of the Study	7
	1.5 Significance of research	8
	1.6 Scope of the Study	8
	1.7 Research Questions and Hypotheses	9
	1.8 Outline of the study	10
	1.9 Summary	11
2	LITERATURE REVIEW	12
	2.1 Introduction	12

2.2	Population impacts of sewage	12
2.3	Rainfall and land se change impacts on sewerage	18
2.4	Sewer discharge and overflow	19
2.4.1	Physical models	20
2.4.2	Statistical models	24
2.5	Wastewater Quality	25
2.5.1	Physical models	25
2.5.2	Statistical models	29
2.6	Sewer overflow mitigation measures	31
2.7	Summary	33
3	RESEARCH METHODOLOGY	34
3.1	Introduction	34
3.2	Modeling Methods	35
3.2.1	Storm Water Managment Model (SWMM5)	35
3.2.2	Multiple-Linear Regression Analysis (LMR)	38
3.2.3	Artificial Neural Network (ANN)	39
3.2.4	Strutural Equation Modeling (SEM)	40
3.3	Study area and data	43
3.3.1	Data Preparation using GIS	43
3.3.2	Description of the study area	43
3.3.3	Soil characteristics of Karbala	45
3.3.4	Sub-catchments of Karaba	48
3.3.4.1	Topography	50
3.3.4.2	Infiltration	51
3.3.4.3	Land use	53
3.3.5	Estimation of pilgrim numbers through pilgrimage	54
3.3.6	Hydraulics data	57
3.3.6.1	Manholes	59
3.3.6.2	Pump station	60
3.3.6.3	Treatment plant	60
3.3.6.4	Sewer lines	61

	3.3.7	Hydrology data	65
	3.3.8	Wastewater quality data	69
	3.3.8.1	Sampling of BOD ₅ and TSS	69
	3.3.8.2	BOD ₅ and TSS testing	70
	3.4	Sewers modeling	70
	3.5	Model calibration and validation	73
	3.6	Pipe-Jacking system	75
	3.7	Summary	78
4		RESULTS AND DISCUSSION	79
	4.1	Introduction	79
	4.2	Results of sewage quantity	79
	4.2.1	Sewage quantity	87
	4.2.2	Sewer discharge modeling using SWMM	86
	4.2.3	Statistical Models	92
	4.2.3.1	Multiple-Linear Regression	93
	4.2.3.2	Artificial Neural Network	105
	4.2.4	Spatial and temporal distribution of sewer overflow	112
	4.2.5	Verification of the model	115
	4.3	Results of sewage quality	115
	4.3.1	Structural Equation Modeling	116
	4.3.2	Multiple Regression Model	125
	4.3.3	Verification of the results	129
	4.4	Technical Measures	130
	4.5	Discussions of sewer quantity and quality	136
	4.6	Summary	138
5		CONCLUSIONS AND RECOMMENDATIONS	139
	5.1	Introduction	139
	5.2	Conclusions	139
	5.3	Recommendations	141

REFERENCES**142**

Appendices A-M

160-277

LIST OF TABLES

TABLE NO.	TITLE	PAGE
3.1	Manning's n – pipe material	37
3.2	Characteristics of Karbala soils	47
3.3	The underground water level	48
3.4	Chemical analysis of groundwater	48
3.5	Characteristics of various soils	52
3.6	Land use within the city of Karbala	53
3.7	The date of the visit to Karbala Arbreen in the Hijri calendar and the Gregorian calendar	55
3.8	The details of the sewerage manholes at the city center of Karbala	60
3.9	The details of the main sewer lines in the city center of Karbala	62
3.10	The details of Karbala city climatology	66
3.11	Rainfall intensities at various frequencies	68
3.12	Confidence range and effective range of calibration and validation	74
3.13	Goodness-of-fit ratings for model calibration	75
3.14	A typical municipal wastewater characterization	75
3.15	Typical characteristics of urban Wastewater	75
4.1	Partial correlation of sewer discharge, population and rainfall	99
4.2	The regression equations showing the relation of population and rainfall with maximum and average sewer flow in Karbala city	100

4.3	Summary statistics for simulated and observed sewer discharge of the reported NSE, R2 and % difference	104
4.4	Sensitivity of sewer flow to population	105
4.5	The percentage of Independent Variable Importance	109
4.6 (a)	Evaluation of convergent validity of the BOD5 concentrations	117
4.6 (b)	Evaluation of convergent validity of the TSS concentrations	118
4.7	Discriminant validity evaluation of the BOD5 and TSS concentrations	119
4.8	Loadings and cross loadings of the BOD5 concentrations	120
4.9	Loadings and cross loadings of the TSS concentrations	121
4.10	The predictive relevance and effect size results of the BOD5 and TSS concentrations	124
4.11	The Collinearity statistics of construal model of the BOD5 and TSS concentrations	124
4.12	Summary of the structural model of the BOD5 and TSS concentrations	125
4.13	The regression equations showing relation of population and rainfall with maximum and average BOD5 and TSS concentrations in Karbala city	128
4.14	Standardized Coefficient of BOD5 and TSS concentrations	128
4.15	Sewage quality values for BOD ₅ and TSS concentrations with 95% confidence interval	129
4.16 (a)	Average sewer discharge for SSL	131
4.16(b)	Maximum sewer discharge for SSL	132
4.17	Details of the suggested sewer line (SSL)	133
4.18	Details of the manholes of the SSL	134

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Floating population of pilgrims in Pandharpur	14
2.2	Population growth in Alandi, India.	14
2.3	Estimates and Projection of China's Floating Population	15
2.4	Population growth and growth of hotels in Puri town during pilgrimage periods	16
2.5	The population concentration in Shanghai	21
3.1	Flow chart of the research	35
3.2	Hypothetical Model of BOD5 and TSS concentrations	42
3.3	Map of Iraq showing Karbala City	44
3.4	Base Map of Karbala, 2006	45
3.5	Soil Map of Karbala generated by GIS	46
3.6	Sub-soil Profile for Karbala city center	46
3.7	Sub-catchment area of Karbala city center (ha)	49
3.8 (a)	The width (m) for each sub-catchment of Karbala city center	49
3.8 (b)	The ground elevation (m)for each sub- catchment of Karbala city center	50
3.9	Elevation map of the city and surrounding areas	51
3.10	Land use of the Karbala city center	54
3.11	Trends in the numbers of pilgrims in Karbala in recent years	56
3.12	The pilgrimage zones through festival days	57

3.13	The sewer networks in the city center of Karbala	59
3.14	The six main sewer lines in the city center of Karbala	61
3.15 (a)	The profile of LINE-1 in the city center of Karbala	63
3.15 (b)	The profile of LINE-2 in the city center of Karbala	63
3.15 (c)	The profile of LINE-3 in the city center of Karbala	64
3.15 (d)	The profile of LINE-4 in the city center of Karbala	64
3.15 (e)	The profile of LINE-5 in the city center of Karbala	65
3.15 (f)	The profile of LINE-6 in the city center of Karbala	65
3.16	The climatological data of Karbala city (1980- 2013)	66
3.17	Rainfall intensity Curve (For Central and Southern Iraq)	67
3. 18	The locations of samples in the city center of Karbala	70
3.19	Peak Factor Curve (Edmonton, 2014)	71
3.20	Typical Diurnal Domestic Wastewater Flow	72
3.21	Typical Diurnal Domestic Wastewater Flow (Steel et al., 1985)	72
3.22	Hydraulic elements of a circular pipe	73
3.23	The Typical steps of PJS	76
3.24	The pipe -jacking system scheme	77
4.1	Population dynamics in Karbala city during two major pilgrimage periods	80
4.2	Distribution of permanent population of Karbala city	81
4.3	Sub-catchment wise distribution of population density of Karbala city during 12 pilgrimage days (Arbaeen visit)	82
4.4	Water consumption at each sub-catchment of Karbala city center (m ³ /day/sub-area) during normal days	83
4.5	The sewer discharge from each sub-catchment of Karbala city center (m ³ /d/subarea) during normal days	83
4.6	Water consumption for each sub-catchment of Karbala city center (m ³ /day/Subarea) during pilgrimage days	84
4.7	Sewer discharge for each sub-area of the Karbala city center (m ³ / Subarea) during 12 days of pilgrimage	85

4.8	The daily distribution of the precipitation of the city center of Karbala (November 2013 to January 2014) using SWMM5	86
4.9	The daily distribution of the infiltration into the sewer system of the city center of Karbala (November 2013 to January 2014) using SWMM5	86
4.10 (a)	Graph of LINE-1 during the normal days.	88
4.10 (b)	Graph of LINE-1 during the pilgrimage days.	88
4.10 (c)	Graph of LINE-2 during the normal days.	89
4.10 (d)	Graph of LINE-2 during the pilgrimage days.	89
4.11 (a)	The timing of sewer discharge in LINE-2	90
4.11 (b)	The timing of sewer discharge in LINE-1	90
4.12 (a)	The water depth distribution in the manholes O37 (LINE-2)	91
4.12 (b)	The water depth distribution in the manholes O38 (LINE-1)	91
4.12 (c)	The head distribution in manhole O37 (LINE-2)	92
4.12 (d)	The head distribution in manhole O38 (LINE-1)	92
4.13 (a)	Average distribution of population, rainfall and sewer discharge during the Muharram period (23-27 November, 2013)	93
4.13 (b)	Maximum distribution of population, rainfall and sewer discharge during the Muharram period (23-27 November, 2013)	94
4.13 (c)	Average distribution of population, rainfall and sewer discharge during Safar period (23rd December, 2013 until 5th January, 2014)	94
4.13 (d)	Maximum distribution of population, rainfall and sewer discharge during Safar period (23rd, December, 2013 until 5th January, 2014)	95
4.14 (a)	Normal P-P plots of observed average and maximum sewer discharge data during Muharram pilgrimage period	95

4.14 (b)	Normal P-P plots of observed average and maximum sewer discharge data during the Safar pilgrimage period	96
4.15 (a)	Average sewer discharge (S.D) dynamic with population during the Muharram period	97
4.15 (b)	Maximum sewer discharge (S.D) dynamic with population during the Muharram period	97
4.15 (c)	Average sewer discharge (S.D) dynamic with population during the Safar period	98
4.15 (d)	Maximum sewer discharge (S.D) dynamic with population during the Safar period	99
4.16 (a)	Histogram and normal P-P plot of the residuals for the average sewer discharge during the Muharram period	100
4.16 (b)	Histogram and normal P-P plot of the residuals for the maximum sewer discharge during the Muharram period	101
4.16 (c)	Histogram and normal P-P plot of the residuals for the average sewer discharge during the Safar period	101
16 (d)	Histogram and normal P-P plot of the residuals for the maximum sewer discharge during the Safar period	102
4.17 (a)	Observed VS. predicted average sewerage discharges during the Muharram period (only 5days), (ISE=2.16 <3 is Excellent Rating)	103
4.17 (b)	Observed VS. predicted maximum sewerage discharges during the Muharram period (only 5days), (ISE=1.885 <3 is Excellent Rating)	103
4.17 (c)	Observed VS. predicted average sewerage discharges during the Safar period (only 15 days), (ISE=1.82 <3 is Excellent Rating)	104
4.17 (d)	Observed VS. predicted maximum sewerage discharges during the Safar period (only 15 days)	106
4.18 (a)	The ANN model used to assess the impacts of population and rainfall on average and maximum	

	sewer discharges during Muharram	106
4.18 (b)	The ANN model used to assess the impacts of population and rainfall on average and maximum sewer discharges during Safar	107
4.19 (a)	Observed VS. Predicted average sewerage discharges during the Muharram period (only 5days)	108
4.19 (b)	Observed VS. Predicted maximum sewerage discharges during the Muharram period (only 5days)	109
4.19 (c)	Observed VS. Predicted average sewerage discharges during the Safar period (only 15 days)	109
4.19 (d)	Observed VS. Predicted maximum sewerage discharges during the Safar period (only 15 days)	110
4.20 (a)	Residuals in prediction of average sewer discharge by ANN during the Muharram period	110
4.20 (b)	Residuals in prediction of maximum sewer discharge by ANN during the Muharram period	111
4.20(c)	Residuals in prediction of average sewer discharge by ANN during the Safar period	111
4.20(d)	Residuals in prediction of maximum sewer discharge by ANN during the Safar period	112
4.121 (a)	Spatial and temporal susceptibility of sewer overflow points during normal periods	113
4.21 (b)	Spatial and temporal susceptibility of sewer overflow points during pilgrimage periods	114
4.22	The time pattern for sewer discharge during pilgrimage	115
4.23(a)	The structural model of BOD5 concentrations	122
4.23(b)	The structural model of TSS concentrations	123
4. 24(a)	Observed vs. predicted BOD5 concentrations during the Muharram period (only 5days) and the Safar period (only 15 days), (ISE=0.502 <3 is Excellent Rating)	126
4.24(b)	Observed vs. predicted TSS concentrations during the	

	Muharram period (only 5days) and the Safar period (only 15 days), (ISE=0.44 <3 is Excellent Rating)	126
4.25(a)	Histogram and normal P-P plot of the residuals for the BOD5 concentrations during the Muharram and Safar period	127
4.25(b)	Histogram and normal P-P plot of the residuals for the TSS concentrations during the Muharram and Safar period	127
4.26	Suggested Sewer Line (SSL) of the Karbala city center by PJS	131
4.27	The boundaries of Zone 1 partially of Karbala city center (2010)	135
4.28 (a)	Wastewater level in SSL during the normal days	135
4.28 (b)	Wastewater level in SSL during the 3rd January pilgrimage day	136

LIST OF ABBREVIATIONS

EPA	-	Environmental Protection Agency
SSO	-	Sewerage Sanitary Overflows
NPS	-	Non-Point Source
DEM	-	Digital Elevation Model
BOD ₅	-	Biochemical Oxygen Demand (Five days)
TSS	-	Total Suspended Solids
SWMM5	-	Storm Water Management Model
ANN	-	Artificial Neural Network
MLR	-	Multivariate Linear Regression
BMPs	-	Best management practices
RDII	-	Rainfall Dependent Inflow and Infiltration
DO	-	Dissolved oxygen
SEM	-	Structural Equation Modeling
MLP	-	Multilayer perceptron
GIS	-	Geographical Information System
DWF	-	Dry Weather Flow
Q _{av.}	-	Average Sewer Discharge
Q _{max.}	-	Maximum Sewer Discharge of Pump Station
P	-	Floating Population
R	-	Rainfall
D	-	Distance of Manhole from City Center

SSL	-	Suggested Sewer Line
PJS	-	Pipe-Jacking System
MM	-	Measurement Model
CR	-	Composite Reliability
AVE	-	Average Variance Extracted

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Some photos for the streets in Zone1, an old Karbala	160
B1	Some photos for Karbala city center before the pilgrimage	161
B2	Some photos for Karbala city center during the pilgrimage	161
C	Daily influx of population in Karbala city during normal and pilgrimage days	163
D	Sewer overflow during the pilgrimage and rainfall periods in Karbala	164
E	The details of the pumps station which are used in the city center of Karbala	165
F	Some photos for the temporary treatments during the pilgrimage and rainfall periods in Karbala	167
G	Some photos for the temporary treatments during the pilgrimage and rainfall periods in Karbala	168
H1	Population density of Karbala city center for the 24 th - 26 th November, 24 th -31 st December 2013 and 1st - 4th January,2014 pilgrimage days	169
H2	Water consumption of Karbala city center for the 24 th - 26 th November, 24 th -31 st December 2013 and 1st - 4th January,2014 pilgrimage days	179
H3	Sewer discharge of Karbala city center for the 24 th -	

	26th November, 24th -31st December 2013 and 1st - 4th January,2014 pilgrimage days	189
I	The report of SWMM5 after simulation process	199
J1	Wastewater level in LINE-1	222
J2	Wastewater level in LINE-2	232
J3	Population and discharges tables	242
K	The spatial and temporal susceptibility of sewer overflow points during pilgrimage periods	247
L	Wastewater level in SSL	266
M	Publication and Conferences	277

CHAPTER 1

INTRODUCTION

1.1 Introduction

Sewage is defined as a combination of liquid wastes (a) conducted away from residences, commercial buildings and industrial establishments; (b) admitted to or find its way into ground, surface, and storm water sewers (Steel et al., 1985; Metcalf and Eddy, 1981; Virtuellier and Der, 2009). Depending on the type of sewage, sewer systems are classified as sanitary, storm or combined. Sanitary sewers carry sanitary sewage produced by the community and industrial waste water. On the other hand, storm sewer carries the surface runoff generated by storms. Storm water often enters sewer networks through poor joints, around manhole covers and other deficiencies (Steel et al., 1985; Metcalf and Eddy, 1981; EPA, 1997). Combined sewers carry all types of sewage in the same conduits (Metcalf and Eddy, 1981). The important goal of sewer networks is the protection of citizens from the diminution of pollution to receiving waters (Hvitved et al., 2013).

Sewer systems are considered as one of the most important components of urban infrastructures (Hahn et al., 2002; Niemczynowicz, 1999; Pitt and Clark, 2008). Sewer networks are usually constructed after considering the peak sewer flows, which are calculated, based on population, per-capita consumption, trade effluent flows and an allowance for infiltration (Atkins, 2011). However, sewage systems are still not properly developed in many cities across the world (Burian et al., 2002; Moore, 2010). Therefore, sudden influx of floating population often causes the failure of sewer systems in such cities. Increasing rainfall intensity due to climate change also becomes a major challenge for sewer systems. These problems are particularly challenging in festival cities where

sudden influx of huge populations often cause huge pressure on existing utility services. Increasing population (temporary or permanent) always leads to increase in dry weather flow, thus increases average sewer discharge based on the Manning equation (Obaid et al., 2014). The sewer systems of many historical or religious cities across the world are not well associated with present day needs. Therefore, an extreme increase in temporary visitors to urban areas during major events like festivals or pilgrimages causes severe impacts on infrastructure, particularly sewer systems. Sanitary sewer overflows (SSO), inundation of roads with sewer and related sanitary and health issues during the pilgrimage period have become a growing concern in such cities in recent years (Obaid et al., 2014).

Rainfall during pilgrimage or festivals often deteriorates the situation. Sudden rainfall after a long dry spell also causes a high level of pollution of storm waters. Rainfall increases runoff volumes and peaks (Burns et al., 2005) and increases the non-point source (NPS) pollution in the runoff (Ying and Sansalone, 2010a; Ying and Sansalone, 2010b). A number of studies in recent years have showed that rainfall causes overflow of sewage systems, regardless of intensity and amount. Therefore, the water quality of receiving water bodies severely deteriorates, particularly during or after rainfall events (Butler and Davies, 2000; Llopart et al., 2014; Freni et al., 2011). Climate change induced-change in rainfall patterns can potentially increase the discharge amount and affect the operation of a sewer system (Abdellatif et al., 2015). It has been reported that nearly 50% of the total pollution in receiving waters is due to sewer overflow (Llopart et al., 2014) and therefore, it is a major challenge in sewer system management. Sewer systems of many cities date back over 100 years. Even recent sewer systems can fail due to huge influx of waste. The sewer networks are constructed beneath the earth. Therefore, signs of degradation and capacity limitations cannot be understood unless there is a major failure. Therefore, impact assessment of population and rainfall on sewer system is very urgent, in order to mitigate sewer failure and avoid environmental hazard.

This chapter presents the background of the problem related to sewer disposal for cities which experience huge temporary floating population. It illustrates sewer problems during festive occasions in countries like China, India, Saudi-Arabia, Italy, etc. and related environmental problems. It also includes the problem statement, objectives, significance and scope of the study.

1.2 Background of the Problem

Sewer management in a city with floating population is a major problem for urban scientists, drainage engineers and policy makers. The problem is challenging for the historic cities, where floating population rises few folds during pilgrimage. Floating population is a terminology used to describe a group of people who reside in a given population for a certain amount of time and for various reasons, but are not generally considered part of the official census count (Sisci and Xiang, 2003). Pilgrimage is a form of travelling to visit places, which is a common custom of most communities. Most of such travelling are motivated by religious desires or tourist's purpose (Gladstone, 2005; Rinschede, 1992; Sharpley and Sundaram, 2005). Pilgrimage tourism seems to be a new academic concept, but is certainly not a new phenomenon (Timothy and Olsen, 2006). Pilgrimage, whether motivated by religious needs or tourist's purpose, is experiencing increasing trend across the world. This includes pilgrimage motivation, pilgrimage activities and tourism influence on pilgrimage (Vijayanand, 2012). A number of studies reported that pilgrimage travel to places have significantly increased in recent decades with improvement in transport infrastructure and accessibility to transport systems (Obaid et al., 2014; Shinde, 2012; Goodkind and West, 2002).

There are many festival cities in the world such as, Moeran (Japan), Mexico Passariello, India (Ichaporia), Sri Lanka west (Kernper), the Central U.S.A (Albers and Williams) and the Caribbean (Lett) (Graburn, 1983). Besides, there are many pilgrimage cities across the world, such as, Mecca, Karbala, Vatican (Italy), and many cities of India. Millions of pilgrims visit shrines in India like Varanasi, Rishikesh, Hardwar, Azmir, Bhubaneswar, Gangotri and Gangasagar, etc. every year. According to Vijayanand (2012), there are nearly 51 festival places (Shakti peethas) in India which are visited by millions of tourists throughout the year. A large number of pilgrims visit the temple of Lord Vitthal all year round, but the number of pilgrims increases drastically during special occasions such as fortnightly full moon days (Ekadashi) (Patange et al., 2013). The Roman Catholic shrines in Lourdes, France received 4,608,000 visitors who came mostly in the short pilgrimage season between April and October (Rinschede, 1986; Eade, 1992). Olympic cities are also examples of cities with a large floating population. The Olympic Games attracted millions of tourists to Olympic cities (Florida et al., 2004; Peiser and Reilly, 2004; Streets et al., 2007; Traversi et al., 2008). For example, the Winter Olympic Games

in Italy attracted almost 2 million spectators during the games period (Traversi et al., 2008) in the cities of Torino, Pavia and Verona. The Guca Trumpet Festival is held annually in Guca village Dragacevo region in western Serbia. The 2-10 days festival attracts up to 600,000 visitors in number (Tadic et al., 2010). Ambaji Temple in India attracts one crore (10 million) pilgrim's annually and approximately 10,000 pilgrims daily. More than three million pilgrims visit the city of Mecca during the pilgrimage period (Al-Hajj). For two days, about 5 million people gather every year in the BiswaEstima (religious gathering) on the bank of Turag River, near the small city of Tangi in Bangladesh (Bisho, 2015). There are many such cities across the world that experience floating population.

The floating population in festival or religious cities has been an issue since ancient times. The ancient Olympic Games that used to hold once in four years were both religious and athletic festivals. It used to attract huge crowds from all over Greece and beyond in a small Olympic city. The city of Mecca is a place of pilgrimage from ancient time. People across the globe used to visit the city during pilgrimage. Therefore, the problem induced by huge floating population is well known from ancient times. With the development of people's well-being and demand for better services, the environmental issues faced during festival or pilgrimage periods have started to generate concern. This has become a major concern in recent years as the total number of population during the peak of festival or pilgrim periods increases in almost all festival or pilgrimage cities across the world. This increase is due to population growth, enhanced ability to move, and more economical ability.

As the world's population continues to increase, and the economy continues to develop, it can be expected that the number of visitors to festival cities during festive periods will continue to grow. The devotees in BiswaEstima in Bangladesh have increased from a few thousands in the early 1980s to about 5 million in recent years. Similarly, the number of pilgrimage tourists is increasing rapidly in most of the pilgrimage centers of India. For example, a small festival town (Alandi) in India used to experience a population of 17,565 in 1981, but increased by 10,249 in 1991. The growth rate was much higher (71.34 %) between 1991 and 2001 (Patange et al., 2013). In Karbala city, the number of pilgrims increased from 10 million in 2009 to 20 million in 2014 (Jafria, 2013; Alkafeel Global Network, 2014). The city of Mecca experienced an increase of pilgrims by 1

million in the last five years. One of the Indian cities, Pandharpur, had 70000 visitors in 1991 but increased to 100000 visitors in 2001 (Patange et al., 2013).

Drastic population increase during pilgrimage or festival period put tremendous pressure on utility services of the city. Huge influx of population during the pilgrimage period also causes many environmental problems in pilgrimage cities. Nevertheless, studies related to anthropogenic environmental problems in pilgrimage cities are still very limited (Shackley, 2001; Tanner and Mitchell, 2002). Massive wastes, particularly the sewers generated by the huge amount of population for a short period are very complex and difficult to handle and thus causes severe environmental threats. A large increase in population causes a high rise in average sewer flow. The biggest bathing days in 2013 in the Ganges River near the Indian city of Allahabad during the holiest day of the festival (KumbhMela) caused an average influx of around two million persons in a day. This caused heavy pollution of the Ganges River in India (Hindustan Times, 2013). The condition of Ambaji Town of Gujarat, which attracts one crore (10 million) pilgrims is deteriorating due to inadequate infrastructure and poor pilgrim facilities; resulting in poor quality of life for residents and pilgrims (GSP, 2009; Soni and Thomas, 2013). Sudden influx of pilgrims in the city of Mecca affects urban services and often disrupts the urban system. The city faces a number of environmental and other urban problems during the pilgrimage period.

The growth of floating population influences the expansion of a city (Ascoura, 2013). Urban areas are characterized by dynamic changes in terms of population structure and land use. Changes in population, living standards of the population, increased per capita water demand, etc., in combination with changes in land-use cause tremendous change in both quantity and quality of sewage discharge. The sewer infrastructure needs to be upgraded from time to time to deal with these dynamics. Inadequate sewage system, improper design and the deterioration of sewer systems over the years make the sewer system incapable of handling the changing dynamics. Furthermore, climate change may intensify rainfall and shorten the flood return period in the future, which may aggravate the situation (Jorgensen et al., 2006). The problem is much severe in historic cities. Usually, huge numbers of people visit pilgrim cities during festive periods and thus, increase the total population of the city by many folds. This huge floating population places enormous pressure on the sewer system of the city. Many of the open areas become sites

for defecation by pilgrims. The network of sewer pipes becomes predominantly choked (FoV, 1998).

The massive wastes generated by the huge population for a short period, are very complex and difficult to handle and this causes severe threats to the environment. Usually, the sewer systems of pilgrim cities are very old and cited in historical locations and therefore, very difficult to modify. Furthermore, it is not possible to build huge sewer systems for the huge population visiting the city only for a particular event in a year. These make solving the sewer problem of pilgrim cities much more complex.

Sewage overflows, inundation of roads with sewer, and related sanitary and health issues during the pilgrimage period have become a growing concern in festival cities in recent years. It is well established that population pressures, land-use conversion and its resulting pollution consequences appear to be the major diffuse pollution problem today (Novotny, 2003; Jabbar, 2011). Urban sewer systems are designed to provide safety and comfort for urban citizens. The role of urban sewer system is much more important in rapidly growing cities. Adaptation measures including redesigning, restructuring, sewer management, etc., are required to mitigate the growing pressure on urban sewer systems in cities.

Sewer overflow during intense rainy season is a major problem in many urban areas across the world. It has been reported that a total of 4,709 properties are at risk of sewer flooding at least once in every ten years in England and Wales (Ofwat, 2011). The flooded area in the Can Tho city of Vietnam increased by up to 50% during similar rainfall events (Tran Van Tu, 2010). Intense rainfall events have also been projected to increase in most parts of the world. Increased urban concentration, urban population and rainfall intensity will certainly increase the incidence of sewer overflow, especially in developing countries, if proper adaptation measures are not undertaken. The problem will be many fold and severe in religious or festival cities where a sudden influx of a huge population puts huge pressure on the existing sewage system. Especially in old religious or pilgrimage cities located in developing countries, sewer overflow and consequent environmental degradation and related public health issues are the most significant urban problem. It has been projected that urban population will reach 60% of the world's population by 2030

(UN, 2005). Intense rainfall events have also been projected to increase in most parts of the world. Research in this regard is very essential as the problem becomes more intricate.

1.3 Statement of the Problem

Sewer management in cities with floating population is a major problem for urban scientists, drainage engineers and policy makers. The problem is challenging for historic festival cities where the floating population rises hundred times during pilgrimage. The problem gradually increases with population growth, improved facilities for public mobility and increased rainfall induced by climate change. As the sewage problem is the major cause of environmental pollution and epidemics during pilgrimage, proffering solution to this problem is extremely important for environmental safety, public health protection and people's comfort. Quantitative estimation of population and rainfall elasticity of both sewer quantity and quality can help to assess how the growing population and changing precipitation pattern will change sewer flow, which in turn can be used for planning, development and management of urban sewer system in the context of environmental change.

1.4 Objectives of the Study

The objectives of the study are as follows:

1. To develop a sewer discharge model to estimate the sensitivity of sewer flow to population.
2. To predict future changes in sewer discharge due to the changes in population and climate.
3. To develop a model for prediction of spatial and temporal susceptibility of sewer overflow.
4. To develop a wastewater quality model in order to assess the sensitivity of sewage quality to population and rainfall.
5. To explore technical measures to mitigate sewer flooding in historic cities which experience high floating population.

1.5 The Significance of the Study

Huge discharge through a sewer system during the pilgrimage period causes sewer overflow, which in turn creates significant problems in terms of environment, public health and psychology. The novelty of this study is to create a model to predict sewer overflow and waste water quality for a sewer system. The model could be applied at any location in the world having similar problems. Furthermore, this study evaluated the maintenance performance of sewage quality, and it is expected to assess the impacts of population and rainfall on urban waste water quality.

Another major importance of the research is that it identifies technical solutions to the problem of a city's sewer system, whose population increases many folds in certain months. The model developed in the research will be able to predict the unknown situation induced by floating population influx and climate change which the city has never faced. Therefore, it will be possible to understand future changes in sewer situations due to population growth and adopt necessary measures to mitigate the impacts.

1.6 Scope of the study

The scopes of the study are as follows:

- a) The study was conducted in the Karbala city center of Iraq, a place where millions of people gather for pilgrimage in the festival months.
- b) The study was based on the available data on population, climate, sewer discharge, wastewater quality (the concentrations of BOD5 and TSS), and extent of sewer and storm networks in the study area.
- c) The maximum sewage flow for the area was considered during the period when maximum rainfall coincides with maximum number of pilgrims.
- d) Land-use of the study area was mapped from LANDSAT data to identify the residential areas.
- e) Information from the Directorate of the Municipality of Karbala was used to demarcate commercial, industrial and public spaces.
- f) The pollution information provided by the Directorate of Population Census was used for the study.

- g) Data on average daily consumption of water per person was collected from the Directorate of Water Supply in Karbala.
- h) Storm Water Management model (SWMM5) and Geographic Information System (GIS) was used to calculate the amplitude of discharge during peak rainfall and maximum pilgrim numbers.
- i) The ratio of sewer deficit to sewer network of the city was used to identify measures required to solve the sewer problem.
- j) Only technical solutions in the context of increasing pilgrims to avoid sewage overflow and environmental pollution were considered.

1.7 Research Questions and Hypotheses

This study aims to answer the following questions. How to simulate sewer overflow and sewer water quality in urban areas that experience sudden influx of population? What mechanisms can be used in a model to analyze sewer systems during pilgrimage periods and rainy season? What are the technical measures that can be used to mitigate sewer flooding in the historical area?

The hypotheses of this research are as follows:

- i. Sewer overflow in the Karbala city center is highly sensitive to population and rainfall in the area.
- ii. Future changes in sewer discharge in Karbala will follow the line of changing floating population.
- iii. Spatial and temporal extents of sewer overflow depends on number of floating population and rainfall amount.
- iv. Sewage quality depends on number of floating population and amount of rainfall.
- v. Technical measures like pipe-jacking system can reduce sewer overflow significantly.

The results and discussion from simple equations of sewer discharge and sewage quality can be verified by comparing with those obtained using a physically-based model of sewer overflow in order to prove that the equations are capable of being a reliable alternative to the physics-based model.

1.8 Outline of the Study

The research work for this study consists of two parts. The first part is to construct models to estimate, modify and examine sewer overflow with a floating population while the second part consists of the experiments to mitigate the problem in festival and historic cities. This thesis consists of five chapters and appendices.

- i. Chapter 1 shows the background of sewer overflow in old and historic cities during pilgrimage days and rainy seasons. The objectives and scope of the study are also mentioned in this Chapter.
- ii. Chapter 2 illustrates previous studies in the world and the methods which had been taken to mitigate sewer overflow.
- iii. Chapter 3 describes detailed discussion of the method used for data collection, analysis and model development in the study.
- iv. Chapter 4 presents the analysis and results obtained by using the methods illustrated in Chapter 3. It also discusses the results obtained from the model application to mitigate sewer overflow and sewage quality with a floating population and rainy seasons. It shows the technical measurements that are adapted to mitigate sewer overflow.
- v. Finally, the conclusions derived from the study together with recommendations for future work are presented in Chapter 5.

1.9 Summary

The research proposal is formulated in this chapter. It highlights the problem statements, objectives of the study, the importance of the research and research questions. From the background analysis of the situation, it can be summarized that sewer management in a city with floating population is a great concern for environmental safety, public health protection and people's comfort in different countries across the world. The concern gradually increases with population growth, improved facilities for public mobility, and increased rainfall induced by climate change. A review of related studies is given in the next chapter.

REFERENCES

- ASCE. (1982). Gravity Sanitary Sewer Design and Construction, ASCE Manual of Practice No. 60, New York, NY.
- An, W., and Gianvito, J. (2010). Kiski Valley WPCA Combined Sewer System Long Term Model Study. In The Annual International Stormwater and Urban Water Systems Modeling Conference Toronto, Canada in 2010 and The Conference Proceeding-Monograph (Vol. 19).
- Aziz, M. A., Imteaz, M. A., Choudhury, T. A., and Phillips, D. I. (2011). Artificial Neural Networks for the prediction of the trapping efficiency of a new sewer overflow screening device. In 19th International Congress on Modelling and Simulation, Perth.
- Aenab, A. and S. Singh. (2011). "Critical Assessment of Environmental Quality of Baghdad, Iraq." *Journal of environmental engineering* 138(5): 601-606.
- Atkins. (2011). Review of sewerage planning and drainage area plans: A report prepared for Ofwat.
- Ascoura, I. E. (2013). Impact of Pilgrimage (Hajj) on the Urban Growth of the Mecca. *Journal of Educational and Social Research*, 3(2), 255.
- Abdellatif, M., Atherton, W., Alkhaddar, R. M., and Osman, Y. (2013). Linking Climate Change to Water Sector: A Case Study of Urban Drainage System.
- Alkafeel Global Network. (2014). <http://alkafeel.net/english/enews/index.php?id=1094>.(2014).
- Ayrault, S., Le Pape, P., Evrard, O., Priadi, C. R., Quantin, C., Bonté, P., and Roy-Barman, M. (2014). Remanence of lead pollution in an urban river system: a multi-scale temporal and spatial study in the Seine River basin, France. *Environmental Science and Pollution Research*, 21(6), 4134-4148.
- Abyaneh, H. Z. (2014 a). Evaluation of multivariate linear regression and artificial neural networks in prediction of water quality parameters. *Journal of environmental health science and engineering*, 12, 2-8.
- Abyaneh, H. Z. (2014 b). Evaluation of multivariate linear regression and artificial neural

- networks in prediction of water quality parameters. *Journal of Environmental Health Science and Engineering* 12, 40.
- Agustsson, J., Akermann, O., Barry, D. A. and Rossi, L. (2014). Non-contact assessment of COD and turbidity concentrations in water using diffuse reflectance UV-Vis spectroscopy. *Environmental Science: Processes and Impacts*, 16(8), 1897-1902.
- Abdellatif, M., Atherton, W., Alkhaddar, R. M., and Osman, Y. Z. (2015). Quantitative assessment of sewer overflow performance with climate change in northwest England. *Hydrological Sciences Journal*, 60(4), 636-650.
- Ai, L., Shi, Z. H., Yin, W. and Huang, X. (2015). Spatial and seasonal patterns in stream water contamination across mountainous watersheds: Linkage with landscape characteristics. *Journal of Hydrology*, 523, 398-408.
- Alnubla. (2015). Microtunneling Process. <http://www.alnubla.net/#!/microtunneling-process/c1yg7> (2015).
- Babbitt. H. E. (1928). *Sewerage and Sewage Treatment*, 3rd edn. Wiley, New York, pp. 28–33.
- Bagozzi, R. P. and Phillips, L. W. (1982). Representing and testing organizational theories: a holistic construal. *Administrative Science Quarterly* 459–489. A8- Vol. 27.
- Butler and David. (1993). The Influence of Dwelling Occupancy and Day of the week on Domestic appliance wastewater discharges. *Building and environment*. Vol.23, No.1, pp.73-79.
- Burian, Steven J., Stephan J. Nix, S. Rocky Durrans, Robert E. Pitt, Chi-Yuan Fan, and Richard Field. (1999). Historical development of wet-weather flow management. *Journal of Water Resources Planning and Management* 125, no. 1 (January/February): 3-13.
- Butler, D. and Davies, J.W. (2000). *Urban Drainage*. London: E&FN SPON.
- Brombach, H., Weiss, G., and Fuchs, S. (2005). A new database on urban runoff pollution: comparison of separate and combined sewer systems. *Water Science and Technology* 51 (2), 119e128.
- Burns, D., Vitvar, T., McDonnell, J., Hassett, J., Duncan, J., and Kendall. C. (2005). Effects of suburban development on runoff generation in the Croton River basin, New York, USA. *Journal of Hydrology*, 311, 266-281.
<http://dx.doi.org/10.1016/j.jhydrol.2005.01.022>. (2013)
- Brown. (2009). Method to prevent base flow interception by gravity sewer line construction.

- <https://www.ieca.org/membersonly/cms/viewabstract.asp?AbstractID=451>(2014).
- Blansett, K. L. (2011). Flow, Water Quality, and SWMM Model Analysis for Five Urban Karst Watersheds (Doctoral dissertation, The Pennsylvania State University).
- Bulat. (2012). Environmental performance indicator for municipal river impacts.
- Bendel, D., Beck, F., and Dittmer, U. (2013). Modeling climate change impacts on combined sewer overflow using synthetic precipitation time series. *Water Science and Technology*, 68(1), 160-166.
- Bisho Istema. (2015). <http://www.ektadoc.com/folio-pdf/130/bisho-istema-rassemblement-de-musulmans.html> (2015).
- Cronbach, L. J. (1951). Coefficient alpha and the internal structure of tests. *Psychometrika*, 16,297-334.
- Crawford, N. H. and Linsley, R. K. (1966). Digital simulation in hydrology: Stanford watershed model IV, Technical Report 39, Dept. of Civil Engineering, Stanford University.
- Cohen, J. (1988). Statistical power analysis for the behavioral sciences. Second Edition. Hillsdale, NJ: Lawrence Erlbaum Associates, Publishers. ACADEMIC PRESS, INC. 111 Fifth Avenue, New York 10003.
- Characklis GW and Wiesner MR. (1997). Particles, metals and water quality in runoff from large urban watershed. *J. Environ. Eng-ASCE*. 123 (8) 753-759.
- Chin, W.W. (1998). Issues and opinions on structural equation modeling. *MIS Quarterly* 22 (1): 7-26.
- Courtenay, G. C., Gladstone, W., and Schreider, M. (2005). Assessing the response of estuarine intertidal assemblages to urbanised catchment discharge. *Environmental monitoring and assessment*, 107(1-3), 375-398.
- Conrads, P. A., Roehl, E. A., Martello, W., and Saxon, E. (2006). The role of artificial neural network models in developing a regional wastewater reclamation facility for beaufort, SC, USA. *International Environmental Modelling and Software Society*.
- Cavanaugh, E. L., Loucks, E. D., and Heinz, S. R. (2007). Using Artificial Neural Networks to Forecast Wet Weather Flow in a Sanitary Sewer System. In *World Environmental and Water Resources Congress 2007@ sRestoring Our Natural Habitat* (pp. 1-8). ASCE.
- Comair, G. (2009). The Waste Water Network: An Underground View of Paris. *Great Rivers History*, American Society of Civil Engineers: 91-98.
- Curran, S. D. (2011). "Life cycle cost model for operating and maintaining wastewater

- sewer systems." *Materials Performance* 50(6): 72-75.
- City population. (2013). Karbala-Iraq Governorates, Regions and Major Cities - Statistics and Maps on City Population. [Http://www.citypopulation.de/Iraq.html](http://www.citypopulation.de/Iraq.html). (2014).
- Coutu, S., Del Giudice, D., Rossi, L., and Barry, D. A. (2012). Parsimonious hydrological modeling of urban sewer and river catchments. *Journal of Hydrology*, 464, 477-484.
- Chatrchyan, S., Khachatryan, V., Sirunyan, A. M., Tumasyan, A., Adam, W., Aguiló, E., and Van Spilbeeck, A. (2013). Search for supersymmetry in events with opposite-sign dileptons and missing transverse energy using an artificial neural network. *Physical Review D*, 87(7), 072001.
- Chèvre, N., Coutu, S., Margot, J., Wynn, H. K., Bader, H. P., Scheidegger, R., and Rossi, L. (2013). Substance flow analysis as a tool for mitigating the impact of pharmaceuticals on the aquatic system. *Water research*, 47(9), 2995-3005.
- Christian, R. A. (2013). *Wastewater treatment: Concepts and design approach*. PHI Learning Pvt. Ltd. 21
- DCSSS. (1968). *Design and construction of sanitary and storm sewers*. Water Pollution Control Federation/ ASCE, New York, N.Y. Manual No.9.
- Djordjevic, S., Prodanovic, D., Maksimovic, C., Ivetic, M., and Savic, D. (2005). SIPSON Simulation of interaction between pipe flow and surface overland flow in Networks. *Water Science and Technology*, 52 (5), 275–283.
- Dodge, Y. (2006). *The Oxford Dictionary of Statistical Terms*, OUP. ISBN 0-19-920613-9.
- Dienhart, A., Erickson, K., Wennen, C., Henjum, M., Hozalski, R., Novak, P., and Frevert, D. K. (2010). In Situ Sensors for Measuring Pollutant Loads in Urban Streams and Evaluating Stormwater BMP Performance. In *Innovations in Watershed Management under Land Use and Climate Change*. Proceedings of the 2010 Watershed Management Conference, Madison, Wisconsin, USA, 23-27 August 2010. (pp. 870-879). American Society of Civil Engineers (ASCE).
- Dawson, C. W., and Wilby, R. L. (2001). Hydrological modelling using artificial neural networks. *Progress in physical Geography*, 25(1), 80-108.
- Drozdova, J., Raclavska, H., and Skrobankova, H. (2013). A survey of heavy metals in municipal wastewater in combined sewer systems during wet and dry weather periods. *Urban Water Journal*, (ahead-of-print), 1-14.
- Directorate of Karbala sewerage. (2013). Report of operation department.
- Directorate of Urban planning of Karbala. (2014). Report of the maintenance. 2014.

- Eade, J. (1992). Pilgrimage and tourism at Lourdes, France. *Annals of Tourism Research*, 19(1), 18-32.
- Environmental Protection Agency (EPA). (1997). Waste water treatment manuals primary, secondary and tertiary treatment. 832-R-04-001.
- Easa, S., and Chan, Y. (2000). Urban planning and development applications of GIS. ASCE.
- Environmental Protection Agency (EPA). (2004). Urban Nonpoint Source Fact Sheet, http://water.epa.gov/polwaste/nps/urban_facts.cfm. (2014).
- Environmental Protection Agency (EPA). (2005). Primer for Municipal Wastewater Treatment Systems.
- Environmental Protection Department (EPD). (2007). Guidelines for Estimating Sewage Flows for Sewage Infrastructure Planning Version 1.0. Report No.: EPD/TP 1/05.
- Edmonton.ca. (2013). Sewer Design Standards and Guidelines. http://www.edmonton.ca/city_government/utilities/sewer-design-standards-guidelines.aspx. (2015).
- Fornell, C. and Larcker, D. F. (1981). Evaluating structural equation models with unobservable variables and measurement error. *Journal of Marketing Research* 48: 39–50.
- Falk, R. F., and Miller, N. B. (1992). A primer soft modeling. Akron, OH: University of Akron Press. Akron, Ohio : University of Akron Press, 1992. https://books.google.com.my/books?id=3CFrQgAACAAJ&dq=A+Primer+for+Soft+Modeling&hl=en&sa=X&ved=0CBwQ6AEwAGoVChMIIttOE7_6VxgIVRX-8Ch1M-ADA. (2014).
- FoV. (1998). Annual FoV Report - Friends of Vrindavan. sharawww.fov.org.uk/india/1998.html. (2013)
- Fenner, R. A. (2000). Approaches to sewer maintenance: a review. *Urban water*, 2(4), 343.
- Florida-James G, Donaldson K, and Stone V. Athens. (2004). The pollution climate and athletic performance. *J Sport Sci Med* 2004;22(10):967–80. <http://www.epa.gov/nrmrl/wswrd/wq/models/swmm/#Applications>. (2015).
- Ferreira, A. P., de Lourdes, C., and da Cunha, N. (2005). Anthropic pollution in aquatic environment: Development of a caffeine indicator. *International journal of environmental health research*, 15(4), 303-311.
- Vallabhaneni, S., Lai, F. H., Chan, C., Burgess, E. H., and Field, R. (2008). SSOAP—a USEPA toolbox for SSO analysis and control planning. In *World Environmental and*

- Water Resources Congress (pp. 1-10).
- Freni, G., Mannina, G., and Viviani, G. (2011). Assessment of the integrated urban water quality model complexity through identifiability analysis. *Water research*, 45(1), 37-50.
- Fu, G., and Butler, D. (2014). Copula-based frequency analysis of overflow and flooding in urban drainage systems. *Journal of Hydrology*, 510, 49-58.
- Fortier, C., and Mailhot, A. (2014). Climate change impact on combined sewer overflows. *Journal of Water Resources Planning and Management*, 141(5), 04014073.
- Gauckler, P. (1867). *Etudes Théoriques et Pratiques sur l'Ecoulement et le Mouvement des Eaux*, Comptes Rendues de l'Académie des Sciences, Paris, France, Tome 64, pp. 818–822 Jump up .
- Geisser, S. (1975). A predictive approach to the random effect model. *Biometrika* 61(1): 101-107.
- Graburn, N. H. (1983). The anthropology of tourism. *Annals of tourism research*, 10(1), 9-33.
- Gaines, J. B. (1989). "Peak sewage flow rate: prediction & probability. *Water pollution Control Federation*, 61(7), 1241-1248.
- Gardner, M. W., and Dorling, S. R. (1999). Neural network modelling and prediction of hourly NO_x and NO₂ concentrations in urban air in London. *Atmospheric Environment*, 33(5), 709-719.
- Gefen, D. and Straub, D. W. (2000). The relative importance of perceived ease of use in IS adoption: a study of e-commerce adoption. *Journal of the Association for Information Systems* 1 (1), 8.
- Gromaire, M. C., Garnaud, S., Saad, M., and Chebbo, G. (2001). Contribution of different sources to the pollution of wet weather flows in combined sewers. *Water research*, 35(2), 521-533.
- Goodkind, D. and West, L. A. (2002). China's floating population: Definitions, data and recent findings, *Urban Studies*, Vol.39:2237-2250.
- Gladstone D.L. (2005). *From Pilgrimage to Package Tour: Travel and Tourism in the Third World*. New York: Routledge.
- Gasperi, J., Kafi-Benyahia, M., Lorgeoux, C., Moilleron, R., Gromaire, M. C., and Chebbo, G. (2008). Wastewater quality and pollutant loads in combined sewers during dry weather periods. *Urban Water Journal*, 5(4), 305-314.
- GSP. (2009). (Gujarat State Portal). (<http://www.gujaratindia.com/about-gujarat/fact->

- file.htm). (2013).
- Gasperi, J., Gromaire, M. C., Kafi, M., Moilleron, R., and Chebbo, G. (2010). Contributions of wastewater, runoff and sewer deposit erosion to wet weather pollutant loads in combined sewer systems. *Water Research*, 44(20), 5875-5886.
- Geza, M., Murray, K. E., and McCray, J. E. (2010). Watershed-scale impacts of nitrogen from on-site wastewater systems: parameter sensitivity and model calibration. *Journal of environmental engineering*, 136(9), 926-938.
- Götz, O., Liehr-Gobbers, K. and Krafft, M. (2010). Evaluation of structural equation models using the partial least squares (PLS) approach. Pp. 691-711. Vincenzo Esposito Vinzi, Wynne W. Chin, Jörg Henseler, Huiwen Wang Springer Science & Business Media, 10 Mar 2010 - Mathematics - 850 pages.
- Gamerith, V., Bertrand-Krajewski, J. L., Mourad, M., and Rauch, W. (2011). Implications of long-term stormwater quality modelling for design of combined sewer infrastructure. *Urban Water Journal*, 8(3), 155-166.
- Gaitan, C. F., Hsieh, W. W., Cannon, A. J., and Gachon, P. (2014). Evaluation of linear and non-linear downscaling methods in terms of daily variability and climate indices: surface temperature in southern Ontario and Quebec, Canada. *Atmosphere-Ocean*, 52(3), 211-221.
- Hulland, J. (1999). Use of partial least squares (PLS) in strategic management research: A review of four recent studies. *Strategic management journal*, 20(2), 195-204.
- Hahn, M. A., Palmer, R. N., Merrill, M. S., and Lukas, A. B. (2002). Expert system for prioritizing the inspection of sewers: Knowledge base formulation and evaluation. *Journal of water resources planning and management*, 128(2), 121-129.
- Hongwei, H., and Xin, H. (2003). 3D Numerical analysis on construction mechanics effect of pipe-jacking [J]. *Chinese Journal of Rock Mechanics and Engineering*, 3, 012.
- Huber, W. (2003). Wet-Weather Treatment Process Simulation Using SWMM. *Watershed Management*, American Society of Civil Engineers: 253-264.
- Hair, J. F. Jr., Black, W. C., Babin, B. J., Anderson, R. E. and Tatham, R. L. (2006). *Multivariate data analysis* (6th Eds.). Upper Saddle River, New Jersey, USA: Prentice-Hall, International Inc.
- Harpham, C., and Dawson, C. W. (2006). The effect of different basis functions on a radial basis function network for time series prediction: a comparative study. *Neurocomputing*, 69(16), 2161-2170.
- Hurlimann, A., Hemphill, E., McKay, J. and Geursen, G. (2008). Establishing components

- of community satisfaction with recycled water use through a structural equation model. *Journal of Environmental Management*, 88(4), 1221-1232.
- Ham, Y. S., Kobori, H., and Takasago, M. (2009). Effects of combined sewer overflow and stormwater on indicator bacteria concentrations in the Tama River due to the high population density of Tokyo Metropolitan area. *Environmental monitoring and assessment*, 152(1-4), 459-468.
- Henseler, J., Christain, M., Ringle, R. and Sinkovics. (2009). The use of partial least square path modeling in international marketing. *Advances in International Marketing* 20: 277-319.
- HOBAS company. (2010).
http://www.hobas.com/fileadmin/Daten/PUBLIC/Brochures_World_pdf/1404_HOBAS_Jacking_Pipes_web.pdf. (2014).
- Hair, J.F., Black, W.C., Babin, B. J., Anderson, R.E. and Tatham. R.L. (2010). *Multivariate data analysis*, 7th edn. Prentice Hall, Upper Saddle River , NJ.
- Hsieh, T. J., Hsiao, H. F., and Yeh, W. C. (2011). Forecasting stock markets using wavelet transforms and recurrent neural networks: An integrated system based on artificial bee colony algorithm. *Applied soft computing*, 11(2), 2510-2525.
- Hair, J. F., Ringle, M. C. and Sarstedt, M. (2011). PLS-SEM: Indeed a silver bullet. *Journal of Marketing Theory and Practice* 9(2): 139-151.
- Hair, J. F., Sarstedt, M., Ringle, C. M. and Mena, J. A. (2012). An Assessment of the use of partial least squares structural equation modeling in marketing research. *Journal of the Academy of Marketing Science* 40 (3), 414–433.
- Hvitved-Jacobsen, T., Vollertsen, J., and Nielsen, A. H. (2013). *Sewer processes: microbial and chemical process engineering of sewer networks*. CRC press.
- Hubbart, J. A. and C. Zell. (2013). "Considering stream flow trend analyses uncertainty in urbanizing watersheds: A base flow case study in the central united states." *Earth Interactions* 17(5).
- Huong, HTL and Pathirana, A. (2013). Urbanization and climate change impacts on future urban flooding in Can Tho city, Vietnam. *Hydrol. Earth Syst. Sci.*, 17, 379–394.
- Hindustan Times. (2013). <http://www.bbc.com/news/world-asia-india-21406879>. (2013).
- Hussein, A. O., Shahid, S., Basim, K. N., and Chelliapan, S. (2015). Modelling Stormwater Quality of an Arid Urban Catchment. In *Applied Mechanics and Materials* (Vol. 735, pp. 215-219).
- Ikram, A. A. (2012). Challenges and trends of using Sewage treatment plants in Islamabad,

Pakistan.

IDRE. 2015. <http://www.ats.ucla.edu/stat/spss/faq/alpha.html> (2015). A15- 22 April, 2015..

Jenkins, C., and Campbell, J. (1996). Catchment areas in general practice and their relation to size and quality of practice and deprivation: a descriptive study in one London borough. *BMJ*, 313(7066), 1189-1192.

Jarvis, D., MacKenzie, S., and Podsakoff, P. (2003). "A Critical Review of Construct Indicators and Measurement Model Misspecification in Marketing and Consumer Research," *Journal of Consumer Research* (30:3), pp. 199-218.

Jorgensen, A., Johansen, R., and Linde, J. (2006). The effect of climate change on urban drainage: an evaluation based on regional climate model simulations. *Water Science and Technology* (S. 9-15). IWA Publishing.

Jacob, J. S. and R. Lopez. (2009). "Is denser greener? An evaluation of higher density development as an urban stormwater-quality best management practice." *Journal of the American Water Resources Association* 45(3): 687-701.

Jabbar H. Al-Baidhani. (2011). Improving of effluent sewage by treatment with local materials. p2.

Jahanbazi, M. and U. Egger. (2013). "Application and comparison of two different dual drainage models to assess urban flooding." *Urban Water Journal*.

Ji, D., Xi, B., Su, J., Huo, S., He, L., Liu, H. and Yang, Q. (2013). A model to determine the lake nutrient standards for drinking water sources in Yunnan-Guizhou Plateau Ecoregion, China. *Journal of Environmental Sciences*, 25(9), 1773-1783.

Jafria. (2013). <http://jafrianews.com/2013/12/20/karbala-ready-to-host-20-million-pilgrims-at-the-event-of-arbaeen-this-year/>.(2013).

Kirpich, Z. P. 1940. Time of concentration of small agricultural watersheds. *Civil Engineering*, 10(6), 362.

Kokkonen, T. S. and A. J. Jakeman. (2001). "A comparison of metric and conceptual approaches in rainfall-runoff.

Kazezyilmaz-Alhan, C. M., M. A. Medina Jr and C. J. Richardson. (2007). "A wetland hydrology and water quality model incorporating surface water/groundwater interactions." *Water Resources Research* 43(4).

Karbala Sewage Project. (2007). 3th and 4th stages, preliminary report. Consulting engineering bureau of Al- Kufa University, Republic of Iraq.

Kurth, A., Saul, A., Mounce, S., Shepherd, W., and Hanson, D. (2008). Application of

- Artificial Neural Networks (ANNs) for the prediction of CSO discharges. In 11th International Conference on Urban Drainage.
- Kock Rasmussen, E., Svenstrup Petersen, O., Thompson, J. R., Flower, R. J., and Ahmed, M. H. (2009). Hydrodynamic-ecological model analyses of the water quality of Lake Manzala (Nile Delta, Northern Egypt). *Hydrobiologia*, 622, 195-220.
- Korving, H., Noortwijk, van J.M., Gelder, van P.H.A.J.M., and Clemens, F.H.L.R. (2009). Risk-based design of sewer system rehabilitation. *Structure and Infrastructure Engineering*, 5 (3), 215–227.
- Kirschbaum, R. and B. Spencer. (2010). Lakewood raincatchers pilot project for reducing combined sewer overflows.
- Kabir, M., Suzuki, M., and Yoshimura, N. (2012). Excess activated sludge reduction by using electromagnets and ferrite particles. *IEEJ Transactions on Electrical and Electronic Engineering*, 7(2), 220-224.
- Krieger, K., Kuchenbecker, A., Hüffmeyer, N., and Verworn, H. R. (2013). Local effects of global climate change on the urban drainage system of Hamburg. *Water Science and Technology*, 68(5), 1107-1113.
- Kuhr, P., Haider, J., Kreins, P., Kunkel, R., Tetzlaff, B., Vereecken, H., and Wendland, F. (2013). Model Based Assessment of Nitrate Pollution of Water Resources on a Federal State Level for the Dimensioning of Agro-environmental Reduction Strategies. *Water resources management*, 27(3), 885-909.
- Kumar, P. S., Jose, A., and James, E. J. (2013). Spatial and Seasonal variation in groundwater quality in parts of Cuddalore District, South India. *National Academy Science Letters*, 36(2), 167-179.
- Lee J. H. and Bang K. W. (2000). Characterization of urban stormwater runoff. *Water Resource*, 34(6), 1773-1780.
- Lenore S. Clesceri, Andrew D. Eaton, Eugene W. Rice. (2005). *Standard Methods for Examination of Water and Wastewater Method 5210B*. Washington, DC: American Public Health Association, American Water Works Association, and the Water Environment Association. <http://www.standardmethods.org> . (2013).
- Leandro, J., Chen, A., Djordjevic, S., and Savic, D.A. (2009). A comparison of 1D/1D and 1D/2D coupled hydraulic models for urban flood simulation. *Journal of Hydraulic Engineering*, 135 (6), 495–504.
- Lim, S., Norzahari, F., and Lee, H. (2010). A GIS-based analysis of potential sewer choke in Western Sydney Region. *KSCE Journal of Civil Engineering*, 14(4), 601-612.

- Lee, S. C., Park, I. H., Lee, J. I., Kim, H. M., and Ha, S. R. (2010). Application of SWMM for evaluating NPS reduction performance of BMPs. *Desalination and Water Treatment*, 19(1-3), 173-183.
- Lee, S., Yoon, C., Jung, K., and Hwang, H. (2010). Comparative evaluation of runoff and water quality using HSPF and SWMM.
- Llopart-Mascaró, A., Farreny, R., Gabarrell, X., Rieradevall, J., Gil, A., Martínez, M., and Paraira, M. (2015). Storm tank against combined sewer overflow: operation strategies to minimise discharges impact to receiving waters. *Urban Water Journal*, 12(3), 219-228.
- Metcalf and Eddy. (1981). *Wastewater engineering: collection and pumping of wastewater*. Tchobanoglous, G., Ed. New York: McGraw-Hill Book Company.
- Maalel, K., and W.C. Huber. (1984). SWMM calibration using continuous and multiple event simulation. In 3rd International Conference on Urban Storm Drainage. Goteborg, Sweden.
- Maidment, David R. (1993). Hydrology. In *Handbook of hydrology*, ed. David R. Maidment, 1.1-15. New York: McGraw Hill.
- Monica Spendilow. (2004). Impeller Magazine, ITT Flygt AB, SE-174 87 Sundbyberg, Sweden. <http://www.islamicfinder.org/Hcal/index.php>
- MPS (2013). Ministry of Public Security, cited in Goodkind and West. (2013).
- Morita, M. (2008). Flood risk analysis for determining optimal flood protection levels in urban river management. *Journal of Flood Risk Management*, 1 (3), 142–149.
- Moore, A. M. (2010). Assessing the demand for simplified stormwater modeling tools within the design profession to facilitate the adoption of sustainable stormwater practices. Mississippi State University.
- Manungufala, T. E., Chimuka, L., Cukrowska, E., and Tutu, H. (2011). Evaluation of the performance of rural wastewater treatment plants using chemical measurements in combination with statistical techniques: a case study. *Toxicological & Environmental Chemistry*, 93(6), 1123-1134.
- Mouri, G., Shinoda, S. and Oki, T. (2012). Assessing environmental improvement options from a water quality perspective for an urban–rural catchment. *Environmental Modelling and Software*, 32, 16-26.
- Maruéjols, T., Lessard, P., and Vanrolleghem, P. A. (2014). Calibration and validation of a dynamic model for water quality in combined sewer retention tanks. *Urban Water Journal*, 11(8), 668-677.

- Mounce, S. R., Shepherd, W., Sailor, G., Shucksmith, J., and Saul, A. J. (2014). Predicting combined sewer overflows chamber depth using artificial neural networks with rainfall radar data.
- MIF. (2014). Makkah, Islamic finder. <http://www.islamicfinder.org/Hcal/index.php>. 2014.
- Messrouk, H., hadj Mahammed, M., Touil, Y., and Amrane, A. (2014). Physico-chemical Characterization of Industrial Effluents from the Town of Ouargla (South East Algeria). *Energy Procedia*, 50, 255-262.
- Muserere, S. T., Hoko, Z., and Nhapi, I. (2015). Fractionation of wastewater characteristics for modelling of Firle Sewage Treatment Works, Harare, Zimbabwe. *Physics and Chemistry of the Earth, Parts A/B/C*. 76–78, 124–133, 2014.
- Manerikar, V. and Manerikar, S. (2015). Cronbach's alpha.
- Niemczynowicz, J. (1999). Urban hydrology and water management—present and future challenges. *Urban water*, 1(1), 1-14.
- Novotny, V. (2003). *Water Quality Diffuse Pollution and Watershed Management*.
- Najafi, M. and G. Kulandaivel. (2005). Pipeline condition prediction using neural network models.
- Oliveira-Esquerre, K. P., Mori, M., and Bruns, R. E. (2002). Simulation of an industrial wastewater treatment plant using artificial neural networks and principal components analysis. *Brazilian Journal of Chemical Engineering*, 19(4), 365-370.
- OWSSB. (2010). Orissa Water Supply and Sewerage Board. *Environmental Impact of Water and Sanitation Issues*.
- Ofwat. (2011). *Summary of a Hydraulic Modelling Exercise Reviewing the Impact of Climate Change, Population and Growth in Impermeable Areas up to Around 2040*. A report prepared for Ofwat, June 2011.
- Olsson, J., and Foster, K. (2014). Short-term precipitation extremes in regional climate simulations for Sweden. *Hydrology Research*, 45(3), 479-489.
- Obaid, H. A., Shamsuddin, S., Basim, K. N., and Shreeshivadasan, C. (2014). "Modeling Sewerage Overflow in an Urban Residential Area using Storm Water Management Model." *Malaysian Journal of Civil Engineering* 26: 163-171.
- Obaid, H. A., Shamsuddin, S., Basim, K. N., and Shreeshivadasan, C. (2014). Modeling Sewer Overflow of a City with a Large Floating Population. *Hydrol Current Res*, 5(171), 2.
- Obaid, H. A., Shamsuddin, S., Basim, K. N., and Shreeshivadasan, C. (2015). "Modelling of wastewater quality in an Urban area during a rainy season". *Asian Journal of*

Microbiology, Biotechnology and Environmental Sciences.

- Pantsar-Kallio, M., Mujunen, S. P., Hatzimihalis, G., Koutoufides, P., Minkkinen, P., Wilkie, P. J. and Connor, M. A. (1999). Multivariate data analysis of key pollutants in sewage samples: a case study. *Analytica chimica acta*, 393(1), 181-191.
- Puerta, J., and Suarez, J. (2002). Contaminant loads of CSOs at the wastewater treatment plant of a city in NW Spain. *Urban Water*, 4(3), 291-299.
- Peiser, B., and Reilly, T. (2004). Environmental factors in the summer Olympics in historical perspective. *Journal of sports sciences*, 22(10), 981-1002.
- Pathiratne, K. A. S., De Silva, O. C. P., Hehemann, D., Atkinson, I., and Wei, R. (2007). Occurrence and distribution of polycyclic aromatic hydrocarbons (PAHs) in Bolgoda and Beira Lakes, Sri Lanka. *Bulletin of environmental contamination and toxicology*, 79(2), 135-140.
- Pallant, J. (2007). *SPSS survival manual: Step-by-step guide to data analysis*, 3rd edn, Allen and Unwin, Australia. McGraw-Hill Education (UK), 1 May 2013 - Psychology - 354 pages.
- https://books.google.com.my/books?id=fZZTBgAAQBAJ&dq=SPSS+survival+manual&lr=&source=gbs_navlinks_s. (2013).
- Pitt, R., and Clark, S. E. (2008). Integrated storm-water management for watershed sustainability. *Journal of Irrigation and Drainage Engineering*, 134(5), 548-555.
- Prigiobbe, V. and M. Giulianelli. (2009). Quantification of sewer system infiltration using $\delta^{18}\text{O}$ hydrograph separation. 60: 727-735.
- Pawlowski, C. W., Rhea, L., Shuster, W. D., and Barden, G. (2013). Some Factors Affecting Inflow and Infiltration from Residential Sources in a Core Urban Area: Case Study in a Columbus, Ohio, Neighborhood. *Journal of Hydraulic Engineering*, 140(1), 105-114.
- Patange, P., Srinithiviahshini, N. D., and Mahajan, D. M. (2013). Pilgrimage and the environment: Challenges in a pilgrimage centre in Maharashtra, India. *International Journal of Environmental Sciences*, 3(6), 2269-2277.
- Park, I. H., Lee, J. Y., Lee, J. H., and Ha, S. R. (2014). Evaluation of the causes of inundation in a repeatedly flooded zone in the city of Cheongju, Korea, using a 1D/2D model. *Water Science and Technology*, 69(11), 2175-2183.
- Rawls, W. J., and Brakensiek, D. L. (1989). Estimation of soil water retention and hydraulic properties. In *Unsaturated flow in hydrologic modeling* (pp. 275-300). Springer Netherlands.

- Rinschede, G. (1992). Forms of religious tourism. *Annals of Tourism Research* 19, 51–67. 219.
- Roe, M.R. (1995). “Guide to Best Practice for the Installation of Pipe Jacks and Microtunnels.” ISBN 0 9525982 0 5. Pipe Jacking Association, London, U.K.
<http://rebar.ecn.purdue.edu/Trenchless/secondpage/Content/PJ.htm>.
- Report of Soil Investigation for Kerbala Pumping Stations Project in Kerbala Governorate (Third Stage). (2007).
- Ryu, J. and Butler, D. (2008). Managing sewer flood Risk, 11th International Conference on Urban Drainage. Edinburgh, UK.
- Rossman, L.A. (2008). Storm Water Management Model User’s Manual (version 5.0). U.S. Environment Protection Agency, Cincinnati, USA.
- Rodríguez, J. P., McIntyre, N., Díaz-Granados, M., and Maksimović, Č. (2012). A database and model to support proactive management of sediment-related sewer blockages. *Water research*, 46(15), 4571-4586.
- Ringle, C. M., Sarstedt, M., Schlittgen, R., and Taylor, C. R. (2012). PLS Path Modeling and Evolutionary Segmentation. *Journal of Business Research*, forthcoming.
- Stone, M. (1974). Cross-validatory choice and assessment of statistical predictions. *J. Roy. Statist. Soc. Ser. B*, 36:111–147. With discussion and a reply by the authors. MR0356377.
- Steel, Terence J. and McGhee. (1985). Water supply and sewerage.
- Schueler, T. (1987). Controlling Urban Runoff: A Practical Manual for Planning and Designing Urban Best Management Practices. MWWOG. Washington, D.C.
- Saget A. and Chebbo G. (1995). Distribution of pollutant loads during rainfall events. CERGRENE/Lyonnaisedes Eaux report, June 1995, 60 p. (in French).
- Shahid, S., Nath, S., and Roy, J. (2000). Groundwater potential modelling in a soft rock area using a GIS. *International Journal of Remote Sensing*, 21(9), 1919-1924.
- Shackley, M. (2001). Managing SacredSites: Service Provision and Visitor Experience. London: Continuum.
- Shahid, S., and Nath, S. K. (2002). GIS integration of remote sensing and electrical sounding data for hydrogeological exploration. *Journal of Spatial Hydrology*, 2(1).
- Shamsi, U. M. and U. M. Shamsi. (2002). GIS tools for water, wastewater, and stormwater systems, ASCE Press.
- Singh, R.P.B. (2002). Sacred space and pilgrimage in hindu society: The case of Varanasi. In R.H. Stoddard and A. Morinis (eds) *Sacred Places, Sacred Spaces*. The

- Geography of Pilgrimages, *Geoscience and Man*, 34(1), pp 191–208.
- Sisci, F., and Xiang, L. (2003). China's Achilles' heel: The 'floating population. *Asia Times Online*.
- Sier, D. A., and Lansey, K. (2005). Monitoring sewage networks for sanitary sewer overflows. *Civil Engineering and Environmental Systems*, 22(2), 123-130.
- Sharpley, R. and Sundaram, P. (2005). Tourism: A sacred journey? The case of ashram tourism, India. *International Journal of Tourism Research* 7, 161–171.
- Suarez, J., and Puertas, J. (2005). Determination of COD, BOD, and suspended solids loads during combined sewer overflow (CSO) events in some combined catchments in Spain. *Ecological Engineering*, 24(3), 199-217.
- Schuurman, N., Fiedler, R. S., Grzybowski, S. C., and Grund, D. (2006). Defining rational hospital catchments for non-urban areas based on travel-time. *International Journal of Health Geographics*, 5(1), 43.
- Streets, D. G., Fu, J. S., Jang, C. J., Hao, J., He, K., Tang, X., and Yu, C. (2007). Air quality during the 2008 Beijing Olympic games. *Atmospheric environment*, 41(3), 480-492.
- Simoes, N., Leitao, J., Maksimovic, C., Marques, S., and Pina, R. (2010). Sensitivity analysis of surface runoff generation in urban flood forecasting.
- Schütze, M., Butler, D., and Beck, B. M. (2011). *Modelling, simulation and control of urban wastewater systems*. Springer Science & Business Media.
- Sun, S. A., Djordjević, S., and Khu, S. T. (2011). A general framework for flood risk-based storm sewer network design. *Urban Water Journal*, 8(1), 13-27.
- Shinde, K. (2012). Policy, planning, and management for religious tourism in Indian pilgrimage sites. *Journal of policy research in tourism, leisure and events*, 4(3), 277-301.
- Soni, H. B., and Thomas, S. (2013). Historical perspectives and future perceptions of sacred pilgrimage spot, central Gujarat, India-A case study of Gomti water tank. *International Journal of Life Sciences Leaflets*, 7, 1-12.
- Senda, T., Maeda, Y., Shimada, H., Sasaoka, T., and Matsui, K. (2013). Studies on Surrounding Soil during Construction using the Deep Pipe Jacking Method in the Deep Strata. *Procedia Earth and Planetary Science*, 6, 396-402.
- Sewerage Manual. (2013). DRAINAGE SERVICES DEPARTMENT. Government of the Hong Kong Special Administrative Region.
- http://www.dsd.gov.hk/EN/Files/publications_publicity/other_publications/technical

- _manuals/Sewerage%20Manual%20Part%201_with%20Eurocodes.pdf. (2014).
- Sanwakizai. (2015). Sanwa Pipe Jacking Machine TS Series.
<http://www.sanwakizai.co.jp/products/small-k/pje-e.html> (2015).
- Temprano, J., and Tejero, I. (2002). Detention storage volume for combined sewer overflow into a river. *Environmental technology*, 23(6), 663-675.
- Tanner, R. and Mitchell, C. (2002). *Religion and the Environment*. New York: Palgrave.
- The Hindu (2001) Acute Water Shortage in Tirumala. Report published on 25 August 2001. <http://www.hinduonnet.com/thehindu/2001/08/25/stories/0425201f.htm>. (2013).
- Timothy, D., and Olsen, D. (Eds.). (2006). *Tourism, religion and spiritual journeys*. Routledge.
- Temprano, J., Arango, Ó., Cagiao, J., Suárez, J., and Tejero, I. (2007). Stormwater quality calibration by SWMM: A case study in Northern Spain. *water SA*, 32(1), 55-63.
- Traversi, D., Degan, R., De Marco, R., Gilli, G., Pignata, C., Ponzio, M., and Bono, R. (2008). Mutagenic properties of PM_{2.5} air pollution in the Padana Plain (Italy) before and in the course of XX Winter Olympic Games of “Torino 2006”. *Environment international*, 34(7), 966-970.
- Tadic, S. D., Griffiths, D., Schaefer, W., Cheng, C. I., and Resnick, N. M. (2010). Brain activity measured by functional magnetic resonance imaging is related to patient reported urgency urinary incontinence severity. *The Journal of urology*, 183(1), 221-228.
- Takamatsu, M., Rangarajan, S., Curry, B., and Palani, S. (2010). Large Interceptor Capacity Analysis Using a Dynamic Hydraulic Model. In *World Environmental and Water Resources Congress, Challenges of Change Proceedings of the World Environmental and Water Resources Congress* (pp. 180-188).
- Tran Van Tu. (2010). (Chairman of the Social Sciences and Humanities Can Tho): Status of some coastal areas related to climate change adaptation and sustainable development of Cuu Long River Delta (MRD).
- Todeschini, S., Papiri, S., and Sconfiatti, R. (2011). Impact assessment of urban wet-weather sewer discharges on the Vernavola river (Northern Italy). *Civil engineering and environmental systems*, 28(3), 209-229.
- Thorndahl, S., Schaarup-Jensen, K., and Rasmussen, M. R. (2013). On hydraulic and pollution effects of converting combined sewer catchments to separate sewer catchments. *Urban Water Journal*, (ahead-of-print), 1-11.

- USEP. (1985). United States Environmental Impact Statement for the East Bay Municipal Utility District Wet Weather Overflow Project. Earth Metrics Incorporated, prepared for the U.S. EPA and East Bay Municipal Utility District, Oakland, Ca.
http://en.wikipedia.org/wiki/Sanitary_sewer_overflow. (2014).
- USEPA. (2002). United States Environmental Protection Agency. Fact sheet: asset management for sewer collection systems. <http://www.epa.gov/npdes/sso>. (2014).
- USAC. (2002). US Army Topographic Engineering Center. 'Hydrologic modeling system (HEC-HMS).
www.hec.usace.army.mil/software/software_distrib/hechms/hechmsprogram.html,
<http://www.waterengr.com/HECHMS.html>. (2015).
- SCS. (2002). US Dept. of Agriculture, Natural Resources Conservation Service, National Water and Climate Center. 'TR-55, urban hydrology for small watersheds.
<http://www.wcc.nrcs.usda.gov/water/quality/common/tr55/tr55.html>.
- UN. (2005). United Nations. Millennium Development Goals Report 2005. New York: UN. United Nations. 2015. Millennium Development Goals Report 2005. New York: UN, UGA. 2013.
<http://extension.uga.edu/publications/detail.cfm?number=C992#ORGANICS>. (2014).
- USEPA (2008). United States Environmental Protection Agency.
file:///C:/Users/USER/Downloads/CSO_CLIMATE_FINAL.PDF. (2014).
- Urbach, N. and Ahlemann, F. (2010). Structural equation modeling in information systems research using partial least squares. *Journal of Information Technology Theory and Application*, 11 (2), pp. 5-40.
- USEPA. (2012). United States Environmental Protection Agency.
http://en.wikipedia.org/wiki/Sanitary_sewer_overflow. (2014).
- Vipulanandan, C. and G. Pasari. (2005). Life Cycle Cost Model (LCC-CIGMAT) for Wastewater Systems. Pipelines. (2005), American Society of Civil.
- Virtueller, A. G. and F. I. Der SiedlungsentwÄsserung. (2009). "Christian Urich."
- Vazquez-Prokopec, G. M., Eng, J. L. V., Kelly, R., Mead, D. G., Kolhe, P., Howgate, J., and Burkot, T. R. (2010). The risk of West Nile virus infection is associated with combined sewer overflow streams in urban Atlanta, Georgia, USA. *Environmental health perspectives*, 118, 1382-1388.
- Vijayanand, S. (2012). Socio-economic impacts in pilgrimage tourism. *Zenith International Journal of Multidisciplinary Research*, 2(1), 329-343.
- VandeWalle, J. L., Goetz, G. W., Huse, S. M., Morrison, H. G., Sogin, M. L., Hoffmann,

- R. G., and McLellan, S. L. (2012). *Acinetobacter*, *Aeromonas* and *Trichococcus* populations dominate the microbial community within urban sewer infrastructure. *Environmental microbiology*, 14(9), 2538-2552.
- Wetzels, M., Odekerken-Schröder, G., and Van Oppen, C. (2009). Using PLS path modeling for assessing hierarchical construct models: Guidelines and empirical illustration. *MIS Quarterly* 33 (1), 177–195.
- Wang, H., Fu, R., Kumar, A., and Li, W. (2010). Intensification of summer rainfall variability in the southeastern United States during recent decades. *Journal of Hydrometeorology*, 11(4), 1007-1018.
- World Weather Information Service, Karbala. (2014). United Nations. <http://worldweather.wmo.int/en/city.html?cityId=1465>. (2014).
- Xizhe, P., Xiuyun, G., and Xuehui, H. (2005). Future Prospects for Population Development in Shanghai. *Asian Population Studies*, 1(3).
- Yoo, J. (2005). "GIS-based simulation of urban sewerage flow volume." *Urban Water Journal* 2(1): 1-12.
- Ying, G., and Sansalone, J. (2010) a. Transport and solubility of Hetero-disperse dry deposition particulate matter subject to urban source area rainfall–runoff processes. *Journal of hydrology*, 383(3), 156-166.
<http://dx.doi.org/10.1016/j.jhydrol.2009.12.030>. (2013).
- Ying, G., and Sansalone, J. J. (2010) b. Particulate matter and metals partitioning in highway rainfall-runoff. *Frontiers of Environmental Science & Engineering in China*, 4(1), 35-46.
- Zhang, H. (2007). "The orientation of water quality variation from the metropolis river - Huangpu River, Shanghai." *Environmental monitoring and assessment* 127(1-3): 429-434.
- Zeferino, J. A., Antunes, A. P., and Cunha, M. C. (2012). Regional Wastewater System Planning under Population Dynamics Uncertainty. *Journal of Water Resources Planning and Management*, 140(3), 322-331.
- Zhen, L., Chen, J. J., Qiao, P., and Wang, J. H. (2014). Analysis and remedial treatment of a steel pipe-jacking accident in complex underground environment. *g Structures*, 59, 210-219.